Regional Service & Customization Centers

China	Taiwan	Netherlands	Poland	USA/ Canada
Kunshan	Taipei	Eindhoven	Warsaw	Milpitas, CA
86-512-5777-5666	886-2-2792-7818	31-40-267-7000	48-22-33-23-740 / 41	1-408-519-3898

Worldwide Offices

Greater China

China
Toll Free	800-810-0345
Beijing	86-10-6298-4346
Shanghai	86-21-3632-1616
Shenzhen	86-755-8212-4222
Chengdu	86-28-8545-0198
Hong Kong	852-2720-5118

Taiwan
Toll Free	0800-777-111
Neihu	886-2-2792-7818
Xindian	886-2-2218-4567
Taichung	886-4-2378-6250
Kaohsiung	886-7-229-3600

Asia Pacific

Japan
Toll Free	0800-500-1055
Tokyo	81-3-6802-1021
Osaka	81-6-6267-1887

Korea
Toll Free	080-363-9494
Seoul	82-2-3663-9494

Singapore
Singapore	65-6442-1000

Malaysia
Toll Free	1800-88-1809
Kuala Lumpur	60-3-7725-4188
Penang	60-4-537-9188

Indonesia
Jakarta	62-21-769-0525

Thailand
Bangkok	66-2-248-3140

India
Toll Free	1-800-425-5070
Bangalore	91-80-2545-0206

Australia
Toll Free	1300-308-531
Melbourne	61-3-9797-0100
Sydney	61-2-9476-9300

Europe

Toll Free	00800-2426-8080

Germany
Munich	49-89-12599-0
Hilden / D´dorf	49-2103-97-885-0

France
Paris	33-1-4119-4666

Italy
Milano	39-02-9544-961

Benelux & Nordics
Breda	31-76-5233-100

UK
Reading	44-0118-929-4540

Poland
Warsaw	48-22-33-23-740 / 41

Russia
Toll Free	8-800-550-01-50
Moscow	7-495-232-1692

Americas

North America
Toll Free	1-888-576-9668
Cincinnati	1-513-742-8895
Milpitas	1-408-519-3898
Irvine	1-949-420-2500

Brazil
Toll Free	0800-770-5355
Saude-São Paulo	55-11-5592-5355

Mexico
Toll Free	1-800-467-2415
Mexico City	52-55-6275-2777

ADVANTECH
Enabling an Intelligent Planet

More Information

8600000063

Embedded Automation Panel Computers

Penetrating Segmented Market by Integrating Control Platforms

- Introduction
- Star Products
- Selection Guide
- Successful Applications

ADVANTECH
Enabling an Intelligent Planet

www.advantech.com

Segmented Automation Panel Solutions

As a leading provider of human machine interface devices, Advantech's HMI products are designed for segmented automation applications to be applied in different industries. With Advantech's HMI, we offer an integrated I/O and control features with HMI/ SCADA software which allows efficient and effective integration and open a new era of automation.

Water treatment

BA

MA

Mining

FA

Marine

Railway

Energy

Oil & Gas

Comprehensive HMI Portfolio

Advantech's comprehensive range of industrial HMI panels has been designed to meet the unique requirements of a wide range of industrial applications. By providing standard and customized products, Advantech supplies their customers with the most flexible automation control panels, thin client panels, industrial monitors and wide screen multi-touch panels. The automation control panels have a compact fanless design and are integrated with multiple IO ports; the thin client panels have a die-cast aluminum alloy front panel and an Intel Atom processor; industrial monitors are rugged units designed to work in tough environments and domain-focus models meet many industrial certification requirements; multi-touch panels not only have built-in intelligent keys for an intuitive UI, but have a 7H hardness anti-scratch display and a 16:9 ratio.

Rugged and Intelligent Panel PC

Powerful Expansion Panel PC

Wide Screen, Multi touch Panels

Multi-function Industrial Monitor

Intelligent Operator Panel

Ruggedized Industrial Monitor

Automation Control Panel

Thin-Client Terminal

Automation Control Panels

Automation Control Panels

- Fanless and compact design
- Integrated with control & IO platforms through Mini PCI-e expansion
- Energy Star certified to reduce power consumption by 30-60%
- "Form and fit" compatible design
- Variety of OS support, including: WES7, Windows XP/XPe, WinCE and Linux

Thin client Panels

Thin client Panels

- Designed with Intel® Atom™ processor
- Compact design with die-cast Al alloy front bezel
- Supports Microsoft® Windows WES7/XP/XPe/CE
- Energy Star approved
- Supports external 2.5" SATA HDD kit

Industrial Monitors

Industrial Monitor

- -20ºC~ 60ºC wide operating temperature range
- Ruggedized design is suitable for harsh environments
- Domain-focused for outdoor, transportation, F&B and oil & gas applications
- Meets diverse industrial requirements with C1D2, EN50155 and IP66 certification

Wide-Screen, Multi-touch Panels

Widescreen, Multi-touch Series

- 16:9 wide screen with PCT multi-touch
- Built-in intelligent and home key button for an intuitive UI
- Anti-scratch surface: 7H hardness
- Front LED indicator to show operating status

Automation Control Panel
TPC-71 Series

With an energy saving LED backlight LCD display, the TPC-71H series is designed with the low power consuming Intel® Atom™ D525 processor 1.8GHz as its core; fanless but with powerful kernel. With PCI-e expansion and DIO control support, the TPC-71H series are designed for automation applications as a control panel solution in a variety of industries.

Compact Expansion
With its compact design, it provides the easiest way to expand the TPC's functionality.

Automation IO Control Module

EtherNet/IP™
PROFINET®
01010101
01010101
01010101

8 x DI/DO design with isolation and Fieldbus control for automation monitoring/control application.

RTC Battery Backup
RTC backup ensures real time data management in case of accidental power failure.

External Antenna
The External Antenna design provides excellent wireless performance.

TPC-671H

6.5" VGA TFT LCD Intel® Atom™ Touch Panel Computer
▶ 6.5" VGA TFT LCD
▶ Intel® Atom Z510 1.1 GHz
▶ Multiple I/O ports for a variety of applications
▶ Mini PCI-e expansion
▶ Integrated 16-channel Digital I/O with isolation
▶ 1 MB Battery-backed SRAM

TPC-1071H

10.4" SVGA TFT LCD Intel® Atom™ Dual-Core D525 Touch Panel Computer
▶ 10.4" SVGA TFT LCD
▶ Intel® Atom D525 1.8 GHz
▶ Multiple I/O ports for a variety of applications
▶ Full-size PCI-e and Mini PCI-e slot
▶ Integrated 16-channel Digital I/O with isolation
▶ 1 MB Battery-backed SRAM

TPC-1271H

12.1" SVGA TFT LCD Intel® Atom™ Dual-Core D525 Touch Panel Computer
▶ 12.1" SVGA TFT LCD
▶ Intel® Atom D525 1.8 GHz
▶ Multiple I/O ports for a variety of applications
▶ Full-size PCI-e and Mini PCI-e slot
▶ Integrated 16-channel Digital I/O with isolation
▶ 1 MB Battery-backed SRAM

TPC- 1571H

15" XGA TFT LCD Intel® Atom™ Dual-Core D525 Touch Panel Computer
▶ 15" XGA TFT LCD
▶ Intel® Atom D525 1.8 GHz
▶ Multiple I/O ports for a variety of applications
▶ Full-size PCI-e and Mini PCI-e slot
▶ Integrated 16-channel Digital I/O with isolation
▶ 1 MB Battery-backed SRAM

TPC-1771H

▶ 17" SXGA TFT LED LCD
▶ Intel® Atom™ D525 1.8 GHz processor
▶ Multiple I/O ports for a variety of applications
▶ Full-size PCI-e and Mini PCI-e slot
▶ Integrated 16-channel Digital I/O with isolation
▶ 1 MB Battery-backed SRAM

Thin-client Terminal
TPC-50/51 Series

Positioned as a thin-client terminal, the TPC-50 series extend their family to the TPC-51 series with Intel® Atom™ platform for 12.1", 15", 17". They are designed with Intel® Atom™ eMenlow XL processors as their core with a low power consumption and wide operating temperature. This system is fanless, has a slim design and the front bezel is die-cast Al alloy material. This product also provides a -20~60° C wide operating temperature solution and complete isolation protection for its serial ports which makes the TPC platform more durable and reliable.

6cm

Slim and Compact
6cm depth fanless design, easy for space-limited installation.

Isolation Protection
2KV isolation protection prevents damage from accidental shock, surges or ground loops.

Wide Temperature
-20ºC ~ 60ºC wide operating temperature range for harsh environment

Wide Temp.
-20ºC 60ºC

Energy Star Certified
Energy-efficient design with Energy Star Certification.

ENERGY STAR

TPC-651H/650H
5.7" VGA TFT LCD Intel® Atom™ Thin Client Computers
▶ 5.7" VGA TFT LED backlight LCD
▶ Intel Z520 1.33 GHz / Intel N270 1.6 GHz
▶ Multiple I/O ports for a variety of applications
▶ Front panel: NEMA4, IP65 certified
▶ TPC-651 with COM port isolation
▶ TPC-651 with wide operating temperatures

TPC-1251H/1250H
12.1" SVGA TFT LCD Intel® Atom™ Thin Client Computers
▶ 12.1" SVGA TFT LED backlight LCD
▶ Intel Z520 1.33 GHz / Intel N270 1.6 GHz
▶ Multiple I/O ports for a variety of applications
▶ Front panel: IP65 certified
▶ TPC-1251 with COM port isolation
▶ TPC-1251 with wide operating temperature range

TPC-1551H/1550H
15" XGA TFT LCD Intel® Atom™ Thin Client Computers
▶ 15" XGA TFT LED backlight LCD
▶ Intel Z520 1.33 GHz / Intel N270 1.6 GHz
▶ Multiple I/O ports for a variety of applications
▶ Front panel: IP65 certified
▶ TPC-1551 with COM port isolation
▶ TPC-1551 with wide operating temperature range

TPC-1750H
17" SXGA TFT LCD Intel® Atom™ Thin Client Computer
▶ 17" SXGA TFT LED backlight LCD
▶ Intel N270 1.6 GHz
▶ Multiple I/O ports for a variety of applications
▶ Front panel: IP65 certified
▶ Dual Gigabit Ethernet supported

Automation Control Panel & Thin-client Terminal Selection guide

Model	TPC-671H	TPC-1071H	TPC-1271H	TPC-1571H	TPC-1771H
CPU	Intel® Atom™ Z510 1.1GHz	Intel® Atom™ D525 1.8 GHz	Intel® Atom™ D525 1.8 GHz	Intel® Atom™ D525 1.8 GHz	Intel® Atom™ D525 1.8 GHz
Memory	1GB SO-DIMM DDR2 SDRAM	4GB SO-DIMM DDR3 SDRAM	4GB SO-DIMM DDR3 SDRAM	4GB SO-DIMM DDR3 SDRAM	4GB SO-DIMM DDR3 SDRAM
Display — Display Type	VGA TFT LED LCD	SVGA TFT LED LCD	SVGA TFT LED LCD	XGA TFT LED LCD	SXGA TFT LED LCD
Display — Display Size	6.5"	10.4"	12.1"	15"	17"
Display — Max. Resolution	640x480	800x600	800x600	1024x768	1280x1024
Display — Max. Colors	262 K	262 K	262 K	262 K	262 K
Display — Luminance cd/m2	700 nits	400 nits	450 nits	350 nits	350 nits
Display — Viewing Angle (H/V°)	160/140	120/100	160/140	160/140	170/160
Display — Backlight MTBF(hrs)	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
Touchscreen	Resistive	Resistive	Resistive	Resistive	Resistive
HDD (Optional)	-	2.5" SATA HDD x 1	2.5" SATA HDD x 1	2.5" SATA HDD x 1	2.5" SATA HDD x 1
Network(LAN)	10/100/1000Base-T x 1	10/100/1000Base-T x 2	10/100/1000Base-T x 2	10/100/1000Base-T x 2	10/100/1000Base-T x 2
I/O ports	RS-232 x 1 RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host)	RS-232 x 2 (with isolation) RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host) PS/2 x 1	RS-232 x 2 (with isolation) RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host) PS/2 x 1	RS-232 x 2 (with isolation) RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host) PS/2 x 1	RS-232 x 2 (with isolation) RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host) PS/2 x 1
CompactFlash	CompactFlash® slot x 1	CompactFlash® slot x 1	CompactFlash® slot x 1	CompactFlash® slot x 1	CompactFlash® slot x 1
Expansion Slots	Mini PCI-E x 1	Mini PCI-E x 1 or PCI-E x 1	Mini PCI-E x 1 or PCI-E x 1	Mini PCI-E x 1 or PCI-E x 1	Mini PCI-E x 1 or PCI-E x 1
Digital Input / Output	-	16-channel Digital I/O with isolation	16-channel Digital I/O with isolation	16-channel Digital I/O with isolation	16-channel Digital I/O with isolation
DC Power Input (Voltage)	18~32V	10~29V	10~29V	10~29V	10~29V
Dimensions	195 x 148 x 44.5 mm (7.68" x 5.83" x 1.75")	287 x 227 x 72.3 mm (11.26" x 8.94" x 2.76")	311 x 237 x 71.6 mm (12.24" x 9.33" x 2.82")	383 x 307 x 78.5 mm (15.08" x 12.09" x 3.09")	414 x 347.5 x 84 mm (16.3" x 13.68" x 3.31")
Weight	0.95 kg (2.1 lbs)	3.5 kg (7.72 lbs)	4.57 kg (10.07 lbs)	5.5 kg (12.13 lbs)	6 kg (13.23 lbs)
Front cover	Front bezel: PC/ABS Resin	Front bezel: Die-cast Aluminum alloy	Front bezel: Die-cast Aluminum alloy	Front bezel: Die-cast Aluminum alloy	Front bezel: Die-cast Aluminum alloy
Operating temperature	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)
Ingress Protection (Front Panel)	IP65	IP65	IP65	IP65	IP65
Certification	CE, BSMI, CCC, UL, FCC Class A	CE, BSMI, CCC, UL, FCC Class A	CE, BSMI, CCC, UL, FCC Class A	CE, BSMI, CCC, UL, FCC Class A	CE, BSMI, CCC, UL, FCC Class A
Operating System	Microsoft® WES7/WES 2009/ XPE/CE 6.0/CE5.0 /Linux / Android	Microsoft® Windows 7/WES7/ WES 2009/XPE/CE 6.0/Linux / Android	Microsoft® Windows 7/WES7/ WES 2009/XPE/CE 6.0/Linux / Android	Microsoft® Windows 7/WES7/ WES 2009/XPE/CE 6.0/Linux / Android	Microsoft® Windows 7/WES7/ WES 2009/XPE/CE 6.0/Linux / Android

Model	TPC-651H	TPC-1251H/1551H	TPC-650H	TPC-1250H/1550H/1750H
CPU	Intel® Atom™ Z520 1.33 GHz	Intel® Atom™ Z520 1.33 GHz	Intel® Atom™ N270 1.6 GHz	Intel® Atom™ N270 1.6 GHz
Memory	1GB SO-DIMM DDR2 SDRAM	1GB SO-DIMM DDR2 SDRAM	1GB SO-DIMM DDR2 SDRAM	2GB SO-DIMM DDR2 SDRAM
Display — Display Type	VGA TFT LED LCD	SVGA/XGA TFT LED LCD	VGA TFT LED LCD	SVGA/XGA/SXGA TFT LED LCD
Display — Display Size	5.7"	12.1"/15"	5.7"	12.1"/15"/17"
Display — Max. Resolution	640 x 480	800 x 600 / 1024 x 768	640 x 480	800x600 / 1024x768 / 1280x1024
Display — Max. Colors	262 K	262 K	262 K	262 K
Display — Luminance cd/m2	700 nits	450/350 nits	700 nits	450/350/350 nits
Display — Viewing Angle (H/V°)	160/140	160/140 160/140	160/140	160/140 / 160/140 / 170/160
Display — Backlight MTBF(hrs)	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
Touchscreen	Resistive	Resistive	Resistive	Resistive
HDD	2.5" SATA x 1 Bundled with Extension HDD Kit (Optional)	2.5" SATA x 1 Bundled with Extension HDD Kit (Optional)	-	2.5" SATA x 1 Bundled with Extension HDD Kit (Optional)
Network(LAN)	10/100/1000Base-T x 2	10/100/1000Base-T x 2	10/100/1000Base-T x 1	10/100/1000Base-T x 2
I/O ports	RS-232 x 1 (With Isolation) RS-422/485 x 1 (With Isolation) USB 2.0 x 2	RS-232 x 1 (With Isolation) RS-422/485 x 1 (With Isolation) USB 2.0 x 2	RS-232 x 2 PS/2 x 1 USB 2.0 x 2	RS-232 x 1 PS/2 x 1 USB 2.0 x 2
CompactFlash	CompactFlash® slot x 1	CompactFlash® slot x 1	CompactFlash® slot x 1	CFast slot x 1
Expansion Slots	-	-	-	-
Digital Input / Output	-	-	-	-
DC Power Input	18~32V	18~32V	18~28V	18 ~ 28V / 18 ~ 32V (TPC-1750H)
Dimensions	195 x 148 x 58 mm	311 x 237 x 54 mm 383 x 307 x 58.1 mm	195 x 148 x 58 mm	311 x 237 x 54 mm / 383 x 307 x 58.1 mm / 413.7 x 347.2 x 63.8 mm
Weight	1.43 kg	2.5 kg /3 kg	1.43 kg	2.5 kg / 3 kg /3.5 kg
Front cover	Front bezel: PC + ABS (TPC-651H)/ Die-cast Aluminum Alloy	Front bezel: PC + ABS (TPC-651H)/ Die-cast Aluminum Alloy	Front bezel: PC+ABS	Front bezel: Die-cast Aluminum alloy
Operating temperature	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	0 ~ 55° C (32 ~ 113° F)	0~55° C (32 ~ 113° F)
Ingress Protection (Front Panel)	IP65	IP65	IP65	IP65
Certification	BSMI, CCC Class A, CE, FCC, UL, Energy Star	BSMI, CCC Class A, CE, FCC, UL, Energy Star	BSMI, CCC Class A, CE, FCC, UL, Energy Star	BSMI, CCC Class A, CE, FCC, UL, Energy Star
Operating System	Microsoft® Windows XP/7/WES7/ WES 2009/ CE 5.0/CE 6.0/ Linux / Android	Microsoft® Windows XP/7/WES7/ WES 2009/ CE 5.0/CE 6.0/ Linux / Android	Microsoft® Windows XP/7/WES7/ WES 2009/ CE 5.0/CE 6.0/ Linux / Android	Microsoft® Windows XP/7/WES7/ WES 2009/ CE 5.0/CE 6.0/ Linux / Android

Wide Screen, Multi touch Panel
TPC-40 series, SPC-40 series, and FPM-7000 series

product design award

2013

Advantech's new range of star products include several new models in the TPC-40 series (Touch Panel Computer), SPC-40 series (Stationary Panel Computer), and FPM-7000 series (Flat Panel Monitors) range of devices, all of which come with 16:9 wide screen multi-touch displays, high-performance dual-core processors, and true flat front IP65 certified touch panels, making them more elegant and suitable for automotive production. By integrating multi-touch functionality, factory workers can increase operational safety with two-point key confirmation and enhance production flexibility.

16:9 Wide screen & Multi-touch
The 16:9 widescreen adds 40% viewing area to display more information for easier management than a traditional 4:3 display. By integrating multi-touch functionality, factory workers can increase operational safety with two-point key confirmation.

Intelligent Keys & Customized UI
Through touch-like intelligent-key support, thin-client panel computers provide an intuitive GUI & usability to simplify operating steps to save time. Customers can easily customize their own UI by using the updated SDK and API released on the official website.

Multi-color LED Indicator
With a multi-color LED indicator, factory workers can quickly realize the computer's operating status. The blue bar indicates the system is working while an orange bar shows that the system is in sleep mode.

Easy-Installation
With a special snap design, the thin-client panel computers can be easily installed by one person thereby speeding up the installation process.

TPC-1840WP/2140WP
18.5" WXGA TFT LCD / 21.5" Full HD Multi-Touch Panel Computer with AMD Dual-core processor
▶ 18.5" WXGA / 21.5" Full HD TFT LED LCD display
▶ AMD dual-core T56E 1.65GHz with independent GPU, advanced graphical performance
▶ 16:9 wide screen with PCT multi-touch
▶ Built-in function and home key button used for intuitive UI
▶ Anti-scratch surface: 7H hardness
▶ Easy Maintenance of Cfast/HDD/Mini-PCIe components by opening side cover
▶ Support Mini-PCIe expansion slot
▶ Support HDMI for second display application
▶ HD Audio supports for alarm application
▶ Front LED indicator to show operating status
▶ IP65 compliant true flat screen
▶ Compact design with Die-cast Magnesium alloy front bezel
▶ Fanless cooling system
▶ Winner of the 2013 iF product design award

SPC-1840WP/2140WP
18.5" WXGA TFT LCD / 21.5" Full HD Stationary Multi-Touch Panel Computer with AMD dual-core processor
▶ 18.5" WXGA / 21.5" Full HD TFT LED LCD display
▶ AMD dual-core 1.65GHz processor with independent GPU, advanced graphical performance
▶ 16:9 wide screen with PCT multi-touch
▶ Built-in function and home key button used for intuitive UI
▶ Anti-scratch touch surface: 7H hardness
▶ All around IP65 with waterproof M12 connector
▶ Support Mini-PCIe expansion slot
▶ Front LED indicator to show operating status
▶ Fanless cooling system
▶ Support standard VESA arm
▶ Winner of the 2013 iF product design award

FPM-7181W/7211W
18.5" / 21.5" Industrial Monitor with Projected Capacitive Touchscreen, Direct-VGA and DVI Ports
▶ 18.5" WXGA / 21.5" Full HD TFT LED LCD display
▶ Truly-flat touch screen with IP65 compliance
▶ Slim type design for Panel mount / Wall mount easy installation
▶ Supports industrial 24VDC power input
▶ Supports panel, wall, desktop and VESA arm mounting
▶ OSD control pad on rear panel
▶ Projected capacitive touch screen, with multi touch.
▶ Robust design with SECC chassis and Magnesium alloy front panel
▶ Lockable I/O connectors

Wide Screen, Multi touch Panel Selection Guide

Model		TPC-1840WP	TPC-2140WP	SPC-1840WP	SPC-2140WP
CPU		AMD® G-series T56E Processor 1.65G	AMD® G-series T56E Processor 1.65G	AMD® G-series T56N Processor 1.6G	AMD® G-series T56N Processor 1.6G
Memory		4GB SO-DIMM DDR3	4GB SO-DIMM DDR3	4GB SO-DIMM DDR3	4GB SO-DIMM DDR3
Display	Display Type	WXGA TFT LED LCD	Full HD TFT LED LCD	WXGA TFT LED LCD	Full HD TFT LED LCD
	Display Size	18.5"	21.5"	18.5"	21.5"
	Max. Resolution	1366 x 768	1920 x 1080	1366 x 768	1920 x 1080
	Max. Colors	16.7M	16.7M	16.7M	16.7M
	Luminance cd/m2	300	300	300	300
	Viewing Angle (H/V°)	170/160	178/178	170/160	178/178
	Backlight MTBF(hrs)	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
Touchscreen		Projected capacitive touch	Projected capacitive touch	Projected capacitive touch	Projected capacitive touch
Network (LAN)		10/100/1000Base-T x 2	10/100/1000Base-T x 2	10/100/1000Base-T x 2, M12 connector	10/100/1000Base-T x 2, M12 connector
I/O Ports		RS-232 x 3 RS-422 / 485 x 1 USB 2.0(Host) x 2 Mic in x 1 Line out x 1	RS-232 x 3 RS-422 / 485 x 1 USB 2.0(Host) x 2 Mic in x 1 Line out x 1	RS-232 x 1 , M12 connector USB 2.0 x 1 , M12 connector 24VDC connector. M12 connector	RS-232 x 1 , M12 connector USB 2.0 x 1 , M12 connector 24VDC connector. M12 connector
HDD (Optional)		2.5" SATA HDD	2.5" SATA HDD	2.5" SATA HDD	2.5" SATA HDD
Intelligent Keys		Quick access through built-in front bezel function and home key button	Quick access through built-in front bezel function and home key button	Quick access through built-in front bezel function and home key button	Quick access through built-in front bezel function and home key button
CompactFlash Slots		CFast slot x 1	CFast slot x 1	-	-
Expansion Slots		Full-sized mini PCI-E x 1	Full-sized mini PCI-E x 1	Full-sized mini PCI-E x 1	Full-sized mini PCI-E x 1
DC Power Input (Voltage)		18 ~ 32 V	18 ~ 32 V	24V	24V
Ingress Protection (Front Panel)		IP65	IP65	All around IP65	All around IP65
Enclosure		Front bezel: Die-cast magnesium alloy Back housing: PC/ABS Resin	Front bezel: Die-cast magnesium alloy Back housing: PC/ABS Resin	Front bezel: Die-cast aluminum alloy Back housing: Die-cast aluminum alloy	Front bezel: Die-cast aluminum alloy Back housing: Die-cast aluminum alloy
Mounting		Panel mount	Panel Mount	Desktop, wall, VESA arm	Desktop, wall, VESA arm
Operating Temperature		0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)	0 ~ 55°C (32 ~ 131°F)
Storage Temperature		-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)
Dimension		488.1 x 309.1 x 56.7 mm (19.2" x 12.2" x 2.2")	580.7 x 355.3 x 56.7 mm (22.8" x 14" x 2.2")	488 x 309 x 65 mm (19.2" x 21.2" x 2.6")	558.4 x 349.8 x 65 mm (21.98" x 13.77" x 2.56")
Weight		7 kg (15.44 lbs)	8 kg (17.64 lbs)	8 kg (17.64 lbs)	9 kg (19.8 lbs)
Certification		BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL
Operating System		Microsoft® Windows XP/7/8/WES7/ WES 2009/CE 6.0/Linux	Microsoft® Windows XP/7/8/WES7/ WES 2009/CE 6.0/Linux	Microsoft® Windows XP/7/8/WES7/ WES 2009/CE 6.0/Linux	Microsoft® Windows XP/7/8/WES7/ WES 2009/CE 6.0/Linux

Model		FPM-7181W	FPM-7211W
CPU		-	-
Memory		-	-
Display	Display Type	WXGA TFT LED LCD	Full HD TFT LED LCD
	Display Size	18.5"	21.5"
	Max. Resolution	1366 x 768	1920 x 1080
	Max. Colors	16.2M	16.7M
	Luminance cd/m2	300	300
	Viewing Angle (H/V°)	170/160	178/178
	Backlight MTBF(hrs)	50,000 hrs	50,000 hrs
Video Port		VGA & DVI-D port	VGA & DVI-D port
Touchscreen		Projected Capacitive touch	Projected Capacitive touch
Network (LAN)		-	-
I/O Ports		RS-232 and USB interface for touch screen	RS-232 and USB interface for touch screen
HDD (Optional)		-	-
Intelligent Keys		-	-
CompactFlash Slots		-	-
Expansion Slots		-	-
Power Input Voltage		Phoenix Jack: 24 V_{DC} input	Phoenix Jack: 24 V_{DC} input
DC Power Input (Voltage)		external 57 W powern adapter, with 100 ~ 240 V_{AC} input and 12 V_{DC} @ 4.75 A output	external 57 W powern adapter, with 100 ~ 240 V_{AC} input and 12 V_{DC} @ 4.75 A output
Ingress Protection (Front Panel)		IP65	IP65
Enclosure		Front panel: Die-cast magnesium alloy Rear cover: SECC	Front panel: Die-cast magnesium alloy Rear cover: SECC
Mounting		Desktop, wall, VESA arm	Desktop, wall, VESA arm
Operating Temperature		0 ~ 50°C (32 ~ 122°F)	0 ~ 50°C (32 ~ 122°F)
Storage Temperature		-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)
Dimension		488 x 309 x 45.7 mm (19.2" x 21.2" x 1.8")	558.4 x 349.8 x 47.7 mm (22" x 13.78" x 1.88")
Weight		6 kg (13.2 lbs)	8 kg (17.6 lbs)
Certification		BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL
Operating System		Microsoft® XP, Vista,7,8, XPe, CE and Linux	Microsoft® XP, Vista,7,8, XPe, CE and Linux

Entry Level Industrial Monitor
## FPM-2000 series

The FPM-2000 series with 12",15"and 17" screens have been designed to fit into areas of limited space without compromising on quality. Their ruggedized all round metal design with IP65 certified fronts ensure that even in harsh environments these monitors will continue to work. The lockable I/O connector design secures the cables and reduces the risk of accidental disconnects. All models have been designed with the same modern look as others in the FPM series and have a reduced front bezel and smaller cut-out dimension size.

Anti-Glare
The anti-glare design cuts down on the amount of light that reflects off the display. This makes the viewing of images and a colors a better experience.

Combo Interface for TouchPanel
Supports both RS-232 and USB interface for touch panel connection to provide flexibility.

Various Mounting Methods
The FPM series are designed to support various mounting methods: wall mount, panel mount, VESA mount, desk mount and rack mount to fit different user environments.

Compact Design
The slim and compact design fits into areas of limited space without compromising on quality.

FPM-2120G
12"SVGA Industrial Monitor with Resistive Touchscreen and Direct-VGA Port

▶ 12'' SVGA TFT LCD with LED backlight
▶ Robust design with aluminum front panel and SECC metal rear cover
▶ Anti-glare screen with tempered glass
▶ Supports Panel, Wall, Desktop, Rack or VESA arm mounting
▶ Combo RS-232 & USB interface for touchscreen function

FPM-2150G
15" XGA Industrial Monitor with Resistive Touchscreen and Direct-VGA Port

▶ 15'' XGA TFT LCD with LED backlight
▶ Robust design with aluminum front panel and SECC metal rear cover
▶ Anti-glare screen with tempered glass
▶ Supports Panel, Wall, Desktop, Rack or VESA arm mounting
▶ Combo RS-232 & USB interface for touchscreen function

FPM-2170G
17" XGA Industrial Monitor with Resistive Touchscreen and Direct-VGA Port

▶ 17'' XGA TFT LCD with LED backlight
▶ Robust design with aluminum front panel and SECC metal rear cover
▶ Anti-glare screen with tempered glass
▶ Supports Panel, Wall, Desktop, Rack or VESA arm mounting
▶ Combo RS-232 & USB interface for touchscreen function

Ruggedized Industrial Monitor
FPM-3000 Series

The FPM-3000 series is a particularly rugged and reliable wide temperature industrial monitor for a variety of industry applications. Equipped with a hard anodized coating, stainless steel chassis, and -20 to 60°C operating temperature, it can satisfy the demands of a wide range of harsh industrial applications. These models also feature enhanced 5-wire resistive touch panels and system ground isolation protection to enhance the reliability, lockable OSD keys on the front panel with two user-defined contrast/brightness settings.

Die-cast Bezel with Stainless Housing

Hard-anodized front bezel design with stainless steel 304 material housing.

Wide Temperature

With an operating temperature range of -20°C ~ 60°C it is designed for use in the harshest environments.

Energy Star Certified

With 33% power consumption reduction and Energy Star Certification.

Grounding Protection

Chassis grounding and power ground protection design to avoid in-rush current damage monitor.

FPM-3121G

12.1" SVGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI and Wide Operating Temperature

▶ 12.1" SVGA LED backlight LCD with low power consumption
▶ Increased reliability with enhanced 5-wire resistive touch sensor
▶ Anti-glare screen with tempered glass
▶ Supports VGA/DVI input, dual touch interfaces and two power inputs
▶ Front lockable OSD membrane keys with user-defined brightness setting
▶ Supports panel, VESA, wall and desktop stand mounting

FPM-3151G

15" XGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI and Wide Operating Temperature

▶ 15" XGA LED backlight LCD with low power consumption
▶ Increased reliability with enhanced 5-wire resistive touch sensor
▶ Anti-glare screen with tempered glass
▶ Supports VGA/DVI input, dual touch interfaces and two power inputs
▶ Front lockable OSD membrane keys with user-defined brightness setting
▶ Supports panel, VESA, wall and desktop stand mounting

FPM-3171G

17" SXGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI and Wide Operating Temperature

▶ 17" SXGA LED backlight LCD with low power consumption
▶ Increased reliability with enhanced 5-wire resistive touch sensor
▶ Anti-glare screen with tempered glass
▶ Supports VGA/DVI input, dual touch interfaces and two power inputs
▶ Front lockable OSD membrane keys with user-defined brightness setting
▶ Supports panel, VESA, wall and desktop stand mounting

FPM-3191G

19" SXGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI

▶ 19" SXGA CCFL backlight LCD with enhanced 5-wire resistive touch sensor
▶ Anti-glare screen with tempered glass
▶ Supports VGA/DVI input, dual touch interfaces and two power inputs
▶ Front lockable OSD membrane keys with user-defined brightness setting
▶ Supports panel, VESA, wall and desktop stand mounting

Multi-function Industrial Monitor
FPM-5000 Series

The FPM-5000G series provides 15", 17" and 19" color TFT LCD flat panel monitors specifically designed for industrial applications. With a viewing size from 15" to 19", they present ample display areas as well as vivid and sharp images. It features Direct-VGA & DVI-D signal transmission, which allows VGA control cards to be used in your system. The onscreen display allows users to adjust the images on the screen with two user-defined settings. The front access USB connector provides easy access the controller, and the industrial 10-30 V_{DC} wide range power support makes this product an excellent option for Factory and Machine Automation display solutions.

Dual Input Functions
Supports VGA/DVI input, dual touch interfaces and two power inputs.

Durable Touch Screen
5-wire exclusive enhance touch feature & high activation force increase normal 250g to 750g.

Lockable IO Connector
ALL I/O connectors such as USB, VGA, DVI and AC power adapter cables are lockable which reduces the risk of accidental disconnects.

Front USB Access
Front accessible USB user friendly design allows easy maintenance in the machine cabinet.

FPM-5151G/5152G

15" XGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI

▶ 15" XGA TFT LCD with resolution up to 1024 x 768
▶ Lockable OSD keys with 2 user-defined contrast/brightness settings
▶ Flat-sealed front panel
▶ Robust design with anti-rust chassis and aluminum die-cast front panel
▶ Front accessible USB connector
▶ Supports industrial 10-30 V_{DC} power input
▶ Support display port input interface on FPM-5152G

FPM-5171G/5172G

17" SXGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI

▶ 17" SXGA TFT LCD with resolution up to 1280 x 1024
▶ Lockable OSD keys with 2 user-defined contrast/brightness settings
▶ Flat-sealed front panel
▶ Robust design with anti-rust chassis and aluminum die-cast front panel
▶ Front accessible USB connector
▶ Supports industrial 10-30 V_{DC} power input
▶ Support display port input interface on FPM-5172G

FPM-5191G/5192G

*19" SXGA Industrial Monitor with Resistive Touchscreen, Direct-VGA, DVI*

▶ 19" SXGA TFT LCD with resolution up to 1280 x 1024
▶ Lockable OSD keys with 2 user-defined contrast/brightness settings
▶ Flat-sealed front panel
▶ Robust design with anti-rust chassis and aluminum die-cast front panel
▶ Front accessible USB connector
▶ Supports industrial 10-30 V_{DC} power input
▶ Support display port input interface on FPM-5192G

Domain-focused Platform

With ultra rugged designs and industrial certifications such as C1D2, EN50155 and IP66, these products are compact and heavy-duty, enabling them to meet the needs of a diverse range of industrial requirements such as outdoor, F&B, railway and oil & gas applications.

316L Stainless Steel

Provides better anti-oxidation, anti-corrosion and anti-bacterial features than normal 304L stainless steel.

Certification

With C1D2, EN50155 and IP66 certification, domain-focused HMI meets diverse industrial requirements.

High Brightness with Optical Bonding

Providing superior sunlight readability with 1000 nits industrial grade LCD display and optical bonding solution is perfect for applications in semi-outdoor or outdoor environments.

User-friendly Design

Use touch gestures to disable or enable touch functionality while cleaning without switching off the power.

TPC-8100TR

10.4" EN50155 Railway Panel Computer

▶ Alternative keypad control in front bezel
▶ Mother board / Daughter board with coating for weather proof
▶ All around IP65 with waterproof M12 connector
▶ Ruggedized enclosure with Die-cast Aluminium alloy
▶ Wide operating temperature: -30 ~ 70°C
▶ EN50155 Compliance for railway application

TPC-1251SR/1551SR

12.1" SVGA / 15" XGA High Brightness LCD Intel® Atom™ Touch Panel PC

▶ Sunlight readable and high luminance solution
▶ 12.1" SVGA / 15" XGA High resolution LED backlight
▶ Wide operating temperature:-20 ~ 60°C
▶ Supports Microsoft® Windows XP / WES7/ XPe / CE / Linux
▶ Energy Star approved

FPM-3151SR

15" XGA High Brightness Industrial Monitor w/ Resistive Touchscreen, Direct-VGA, DVI and Wide Operating Temperature

▶ High luminance solution for sunlight readable
▶ 15" XGA high resolution LED backlight
▶ Wide operating temperature:-20 ~ 60°C
▶ Increased reliability with enhanced 5-wire resistive touch sensor and ITO film
▶ Supports VGA/DVI input, dual touch interfaces and two power inputs

FPM-8151H / FPM-3171S / FPM-3191S

15" XGA Industrial Monitor for Hazardous Location, with 316L Stainless Steel Front Panel

▶ UL CID2 certified for hazardous locations
▶ 15" XGA TFT LCD with LED backlight
▶ Stainless steel 316L front panel
▶ IP65 compliant front panel
▶ Wide operating temperature:-20 ~ 60°C

17"/19" SXGA Industrial Monitor with Resistive Touchscreen, Direct-VGA and DVI Ports

▶ Robust design with 316L level stainless steel chassis and front panel
▶ Supports panel, wall, desktop, VESA arm mounting

FPM Series Selection Guide

| Model	FPM-2120G/2150G/2170G	FPM-3121G/3151G/3171G/3191G	FPM-5151G/5171G/5191G	FPM-5152G/5172G/5192G
CPU	-	-	-	-
Memory	-	-	-	-
Display / Display Type	12" SVGA / 15" XGA / 17" XGA	12" SVGA / 15" XGA / 17" SXGA / 19" SXGA	15" XGA / 17" SXGA / 19" SXGA	15" XGA / 17" SXGA / 19" SXGA
Display / Display Size	12"/15"/17"	12"/15"/17"/19"	15"/17"/19"	15"/17"/19"
Display / Max. Resolution	800x600 / 1024x768 / 1024x768	800x600 / 1024x768 / 1280x1024 / 1280x1024	1024 x 768 / 1280 x 1024 / 1280 x 1024	1024 x 768 / 1280 x 1024 / 1280 x 1024
Display / Max. Colors	16.2M / 16.2M / 16.7M	16.2M / 16.2M / 16.7M / 16.7M	16.2M / 16.7M / 16.7M	16.2M / 16.7M / 16.7M
Display / Luminance cd/m2	450 / 400 / 350	450 / 350 / 350 / 350	400 / 350 / 350	350 / 350 / 350
Display / Viewing Angle (H/V°)	160/140 / 160/140 / 170/160	160/140 / 160/140 / 170/160 / 170/160	160/140 / 170/160 / 170/160	160/140 / 170/160 / 170/160
Display / Backlight MTBF(hrs)	50,000	50,000	50,000	50,000
Video Port	VGA	VGA/DVI	VGA/DVI	Display port
Touchscreen	Combo	Combo	Combo	USB
Network(LAN)	-	-	-	-
I/O ports	-	-	-	-
HDD(Optional)	-	-	-	-
OSD(onscreen display)	On rear side with lockable function	On front Panel with lockable function	On rear side with lockable function	On rear side
CompactFlash Slots	-	-	-	-
Expansion Slots	-	-	-	-
DC Power Input	12v	12v & 24v	10-30v	18-32v
Ingress Protection(Front Panel)	IP65	IP65	IP65	IP65
Enclosure	Front panel: Aluminum with coating Rear cover: SECC coating chassis	Front panel: Aluminum with hard anodizing coating Rear cover : Stainless steel Ground Isolation Protection	Front panel: Aluminum and flat-sealed Rear cover: Anti-rust coating	Front panel: Aluminum and flat-sealed Rear cover: Anti-rust coating
Mounting	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm
Operating temperature	0~50°C	-20~60°C / -20~60°C / -20~60°C / 0~50°C	0~50°C	0~50°C
Storage Temperature	-20~60°C	-30~80°C / -30~80°C / -30~80°C / -20~60°C	-20~60°C	-20~60°C
Dimension	311 x 237 x 40.63mm / 383 x 307 x 48 mm / 413.72 x 347.22 x 52.13mm	312 x 224 x 60 mm / 422 x 310 x 70 mm / 482 x 354.8 x 63.9mm / 482 x 399 x 67 mm	449.92 x 315.63 x 50.5 mm / 481.9 x 355.9 x 55 mm / 481.93 x 384.6 x 59 mm	449.92 x 315.63 x 50.5 mm / 481.9 x 355.9 x 55 mm / 481.93 x 384.6 x 59 mm
Weight	4kg / 4.5kg / 5.6kg	4.07kg / 7.73kg / 9.25kg / 10.65kg	6kg / 8kg / 10kg	6kg / 8kg / 10kg
Certification	BSMI, CCC, CE, FCC Class A, UL	FPM-3121G/3151G : BSMI, CCC, CE, FCC Class A, UL Energy Star FPM-3171G/3191G : BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL
Operating System	Windows XP, Vista, 7,8, XPe, CE and Linux	Windows XP, Vista, 7,8, XPe, CE and Linux	Windows XP, Vista, 7,8, XPe, CE and Linux	Windows XP, Vista, 7,8, XPe, CE and Linux
Touch Operation System	PenMount 6000	FPM-3121G/3151G : PenMount 6000 FPM-3171G/3191G : Elo Touch	PenMount 6000	PenMount 6000

Domain-focused selection guide

Model	TPC-1251SR/1551SR	FPM-3151SR	FPM-3171S/3191S	FPM-8151H	TPC-8100TR
CPU	Intel Atom 1.33 GHz with 512KB cache	-	-	-	Intel ATOM N2600 Dual core processor 1.6G
Memory	1GB SO-DIMM DDR2 667 SDRAM	-	-	-	4GB SO-DIMM DDR3 SDRAM
Display / Display Type	SVGA / XGA	XGA	SXGA	XGA	SVGA
Display / Display Size	12.1"/15"	15"	17"/19"	15"	10.4"
Display / Max. Resolution	800 x 600 / 1024 x 768	1024x768	1280 x 1024	1024 x 768	800 / 600
Display / Max. Colors	262 K	16.2 M	16.2 M	16.2 M	262 K
Display / Luminance cd/m2	1000	1000	350/300	350	400
Display / Viewing Angle (H/V°)	110/160 / 120/140	125/140	170/160 / 170/160	160/140	160/140
Display / MTBF(hrs)	50,000	50,000	50,000	50,000	50,000
Touchscreen	Resistive	Combo	Resistive	Resistive	internal USB
Network(LAN)	10/100/1000Base-T x 2	-	-	-	100/1000 Base x 2
I/O ports	RS-232 x 1 (with isolation) RS-422/485 x 1 (with isolation) USB 2.0 x 2 (Host)	VGA/DVI-D	VGA & DVI-D	VGA & DVI-D	RS-232 x 2(connection: M12 A-coded,8-pin male) RS-422/485 x 2(with isolation, connection: M12 A-coded, 8-pin male) USB 2.0 x 2(connection: M12 A-coded, 8-pin female) Audio x 1(with Internal Buzzer, Line out, connection: M12 A-coded, 8-pin male) Power connector x 1(connection: M12 A-coded, 5-pin male)
HDD(Optional)	2.5" SATA HDD x 1	-	-	-	-
OSD(onscreen display)	-	On front panel with lockable function	On front panel with lockable function	On front panel with lockable function	-
CompactFlash Slots	CompactFlash Slot x 1	-	-	-	build in 16G Cfast
Expansion Slots	-	-	-	-	-
DC Power Input	18~32v	12v & 24v	24v	24v	110v
Ingress Protection(Front Panel)	IP65	IP65	IP65	IP65	all around IP65
Enclosure	Front bezel: Die-cast Aluminum alloy Back housing: SECC	Front panel: Aluminum with hard anodizing coating Rear cover : Stainless steel Ground Isolation Protection	Front panel: Stainless steel with 316L level Rear cover: Stainless steel chassis	Front panel: 316L Stainless steel Rear cover : Stainless steel Ground Isolation Protection	Front bezel: Die-cast Aluminium alloy Back housing: Die-cast Aluminium alloy
Mounting	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm	Panel, wall, desktop, VESA arm	Panel, VESA arm
Operating temperature	-20~60°C	-20~60°C	-20~60°C / 0~50°C	-20~60°C	-30~70°C
Storage Temperature	-30~80°C	-30~80°C	-30~80°C / 20~80°C	-20~60°C	-30~70°C
Dimension	311 x 237 x 54 mm 383 x 307 x 58.1 mm	422 x 310 x 70 mm	462.8 x 378.4 x 63.9 mm 489.3 x 408.6 x 68 mm	422 x 338 x 68 mm	345 x 227 x 85 mm
Weight	2.5 kg / 3 kg	7.73 kg	13.1 kg / 15 kg	8.5 kg	5 kg
Certification	BSMI, CCC, CE, FCC Class A, UL	CE, FCC Class A, CCC, UL, Energy Star	CE, FCC Class A, BSMI, CCC, UL	CE, FCC Class A, UL C1D2, BSMI, CCC	CE, FCC Class A, CCC, UL, EN50155
Operating System	Windows XP/WES7/XPe/CE/Linux	Windows 2000, XP, Vista, 7, 8, XPe, CE and Linux	Windows 2000, XP, Vista, 7, 8, XPe, CE and Linux	Windows 2000, XP, Vista, 7, 8, XPe, CE and Linux	Windows XP,7, 8, WES 2009, WES7, CE 6.0 and Linux

HMI Application Story Overview

Coal Mine Automation System of Weight Checking and Fraud Prevention

Coal is transported from the mine to a warehouse therefore, to ensure that the correct weight and products arrive at the warehouse, a method of checking is required. To build the platform for this application, Advantech's industrial touch panel monitor, FPM-3121G which features wide-temperature and sunlight readability making it especially suitable for outdoor applications. All the information is collected and transmitted via the EKI-1526 to the UNO-2050G, and the data is then sent to the central control room, and is shown not only on the FPM-3121G monitor. The design of Advantech's products allows for stable and reliable operation in ultra-harsh outdoor environments such as coal mines

Central Control Room
FPM-3121G
Ethernet
EKI-1526
UNO-2050G
Traffic Light
LED Display · Camera · RFID Reader & Signal Transfer · Card Reader

Batch control system in Silicon Crystal grower & Diffusion furnace Application

In order to achieve a high quality solar cell, Silicon crystal material treatment & diffusion furnace are raw material treatment process devices. It is a very high temperature control furnaces, around 1600 degC , and need a high reliable, stability & powerful operation station for operating, monitoring & integration to control center .

For building the platform for this application, Advantech's Embedded Automation Panel TPC-1571H is used as master workstation in control center to monitor the information transmitted via the EKI-1526 and Supervisor s/w WebAccess, to operate the process through APAX-5000 Amonet Network for motion control. This design of Advantech's products allows stable and reliable operation in such ultra-harsh environment for Silicon crystal material treatment & diffusion furnace application.

TPC-1571H
EKI
Controller : APAX
Temperature · Heater · Push buttons · Indicators

Surveillance and Monitoring System over Power Substations in Beijing Subway

Advantech's Embedded Automation Panel TPC-1750H is used in the power substations of one of the Beijing Subway lines. In each substation, there are meters and other terminal devices monitoring the status of the transformer, the use of power, temperature and pressure. To monitor the substations' activity from a control room, the Advantech TPC-1750H 17" SXGA TFT LCD Intel® Atom™ Thin Client Computer together with EKI-7656C and uno-4672 was proposed, offering remote out-of-band manageability, improved data transmission and security, and energy efficient performance. It is the excellent choice for subway substation monitoring and surveillance systems.

Central Control Room
TPC-1750H
EKI-7656C
Redundant X-ring Recovery Time<10ms
EKI-7656C
UNO-4672
UNO-4672
IED · IED · IED · Transducer · IED · Controller

MES control system for automotive engine assembling line in China

With several production lines at their manufacturing plant, a global car manufacturer was keen to speed up their productivity whilst increase quality and reduce error rate. For workers to have the flexibility to choose from a range of components, management required workers to have access to multi-touch panel computers to improve the tracking of each part of the assembly line. If there was a failure during any part of the process the client required that assembly workers could fix it quickly through the use of the panel so that the line wouldn't be held up.

With an outstanding price performance ratio, the iF Award winning TPC-1840WP and TPC-2140WP are exemplified not only by their appearance but also by their intuitive user interface. With their two pale blue soft-keys that, when lightly touched, give users quick and easy access to the information they need, the TPC-1840WP and 2140WP allow convenient viewing of information. To further aid this, both models feature wide screens with a ratio of 16:9 and multi-touch capabilities to provide more screen area and greater control as well as viewing of information.

Our client tested several other manufacturers during the consultation process and it was decided that Advantech offered the best overall solution with the most up-to-date panel PCs, the ability of these systems to be installed anywhere in the world and be guaranteed of the same quality of service they are receiving in their Italian plant; Advantech's post-sales technical support gives the customer assurances that any difficulties will be handled quickly and efficiently to ensure that there is no loss of services; and finally the all-in-one solution which not only included the hardware but also the installation and configuration of the clients bespoke software.